

# METHOD AND APPARATUS FOR OBSERVING NETWORK-SAFETY ENSURING POLICY IN PUBLIC KEY CRYPTOGRAPH SYSTEM

**Publication number:** JP5216411 (A)

**Publication date:** 1993-08-27

**Inventor(s):** SUTEFUAN EMU MATEIASU; DONARUDO BII JIYONSON; AN BUI RII; UIRIAMU SHII MAATEIN; ROSUTEISUROU PURAIMATSUKU; UIRIAMU ESU ROORANDO; JIYON DEI UIRUKINSU +

**Applicant(s):** IBM +

**Classification:**

- **international:** **G06F21/00; G09C1/00; H04L9/08; H04L9/32; G06F1/00; G06F21/00; G09C1/00; H04L9/08; H04L9/32; G06F1/00; (IPC1-7): G09C1/00**

- **European:** G06F21/00N1D1; H04L9/08C; H04L9/32

**Application number:** JP19920261293 19920930

**Priority number(s):** US19910786227 19911031

**Also published as:**


JP2552061 (B2)  
US5164988 (A)  
EP0539726 (A2)  
EP0539726 (A3)  
EP0539726 (B1)

[more >>](#)

## Abstract of JP 5216411 (A)

**PURPOSE:** To provide an improvement method for key management in a public key cipher system.

**CONSTITUTION:** A device A continues to faithfully execute a safety guaranteeing policy instructed by an authorization center 10 as long as the public key PUMa of the device A is authorized. When the device A changes the operation from the ciphered limit of an old constitution vector by the loading of a new constitution vector for instance, the participation to the network of the device A is denied. In order to achieve the execution of the network safety guaranteeing policy instructed by the authorization center 10, it is required to make the authorization center 10 recognize that the device A is constituted of an authenticated present constitution vector at the point of time when the device A requests the authorization of the public key PUMa.



Data supplied from the **espacenet** database — Worldwide